

CK, CKT, & CK Trend Technical Data

Technical Data



Certified to ANSI/UL Std. 2021
Conforms to CAN/CSA Std. 22.2 No. 46



Model	CK 15 E	CKT 15 E	CK 20 E		CKT 20 E		CK 150-1 Trend	CK 200-2 Trend		
Item number	074058	230345	074057		230346		236304	236305		
Voltage	120 v	120 v	240 v or 208 v		240 v or 208 v		120 v	240 v or 208 v		
Wattage	1500 w	1500 w	2000 w	1500 w	2000 w	1500 w	1500 w	2000 w	1800 w	
Amperage	12.5 A	12.5 A	8.3 A	7.2 A	8.3 A	7.2 A	12.5 A	8.3 A	8.7 A	
Rated output Btu/hr	5118	5118	6824	5118	6824	5118	5118	6824	6142	
Recommended circuit breaker size¹	15 A	15 A	15 A		15 A		15 A	15 A		
Minimum wire size (copper)	14 AWG	14 AWG	14 AWG		14 AWG		14 AWG	14 AWG		
Timer	no	yes	no		yes		N/A	N/A		
Heating element	nichrome wire						ceramic positive temperature coefficient (PTC)			
Thermostat & high limit	bimetal type						bimetal type			
Motor	18 w shaded pole						20 w shaded pole			
Blower	galvanized steel, squirrel cage type						glass-reinforced polycarbonate, radial type			
Dimensions	18 7/8" / 460 mm H x 13 3/16" / 335 mm W x 4 13/16" / 123 mm D						15 3/4" / 400 mm H x 10 7/8" / 275 mm W x 5 1/8" / 131 mm D			
Weight	8.0 lb / 4.4 kg						5.5 lb / 2.5 kg			
Temperature range	41°F - 86°F / 5°C - 30°C						45 - 95 °F / 7 - 35 °C			
Frost protection setting	45°F / 7°C						45°F / 7°C			
Operating noise	49.7 dB(a)						49.0 dB(a)			

¹ This is our recommendation as the manufacturer. Check local codes for compliance if necessary.